

uPVC High Pressure ASTM Threaded Pipes

A Supreme way for lifelong supply of Pure and Safe drinking water

The Supreme Industries Ltd., is an acknowledged leader of India's plastic industry. It is credited with pioneering several path breaking products and has valuable experience in providing innovative and cost effective piping solution. Company's objective is to meet the growing needs of its clientele in water, waste management and infrastructure sector through specially developed high performance range of piping products. The innovative product portfolio offered by Supreme is extensive in range and application and comprises a variety of pipes and a vast spectrum of fittings totaling around 7000 diverse products. Together these constitute the most comprehensive range in the industry that caters almost every conceivable need and application. Company has been a torch bearer in transition from conventional products to advance plastics piping products in the country and has been termed as "Trend Setters of Plastic Piping Products".

Supreme threaded pipes are manufactured as per ASTM standards. They are one of the many products that are offered by the company. These pipes have several features that are par excellence.



FEATURES AND BENEFITS :

- ▶ Stronger, resilient and longer lasting
- ▶ Excellent corrosion and chemical resistance
- ▶ Light weight, easy and fast installation
- ▶ Hygienic and safe for carrying drinking water
- ▶ Optimum flow rates
- ▶ Unaffected by termites, fungus or bacteria
- ▶ No algae formation
- ▶ 100% Leak proof joints
- ▶ No root penetration
- ▶ No galvanic action with CP and other fittings
- ▶ Bad conductor of electricity
- ▶ Available in SCH-40, SCH-80, SCH-120
- ▶ Economical, low operating and maintenance cost
- ▶ Well accepted by the users in India and abroad

These pipes are manufactured as per ASTM D 1785 standard and are available in SCH 40, 80 and 120 pressure class. These pipes are generally used for plumbing, water supply and for lowering jet pumps in the borewells. These pipes are not recommended to use with aqua gold fittings. ASTM threaded pipes are 40-50% cheaper to G.I. pipes and offer all the advantages of aqua gold pipes. Dimensions and pressure ratings of these pipes are given in the table below.


**Dimensions and water pressure rating at 23°C for pipes as per ASTM D-1785 and threads as per IS-554
(PVC compound grade equivalent to PVC 1120/2120)**

Nominal Size		Outside Diameter (D) in mm	Schedule 40				Schedule 80				Schedule 120			
			Wall Thickness (t) in mm	Working Pressure		Wall Thickness (t) in mm	Working Pressure		Wall Thickness (t) in mm	Working Pressure		Wall Thickness (t) in mm	Working Pressure	
mm	inch			Kgf/cm ²	psi		Kgf/cm ²	psi		Kgf/cm ²	psi		Kgf/cm ²	psi
15	½	21.34 ± 0.10	2.77 + 0.51	20.7	300	3.73 + 0.51	29.0	420	4.32 + 0.51	35.2	510			
20	¾	26.67 ± 0.10	2.87 + 0.51	16.5	240	3.91 + 0.51	23.4	340	4.32 + 0.51	26.9	390			
25	1	33.40 ± 0.13	3.38 + 0.51	15.5	225	4.55 + 0.53	22.1	320	5.08 + 0.61	24.8	360			
32	1¼	42.16 ± 0.13	3.56 + 0.51	12.7	185	4.85 + 0.58	17.9	260	5.46 + 0.66	20.7	300			
40	1½	48.26 ± 0.15	3.68 + 0.51	11.4	165	5.08 + 0.61	16.5	240	5.72 + 0.68	18.6	270			
50	2	60.32 ± 0.15	3.91 + 0.51	09.6	140	5.54 + 0.66	13.8	200	6.35 + 0.76	16.5	240			
#65	2½	75.20 ± 0.10	5.16 + 0.61	10.3	150	7.01 + 0.48	14.5	210	7.62 + 0.91	15.9	230			
80	3	88.90 ± 0.20	5.49 + 0.66	08.9	130	7.62 + 0.91	13.1	190	8.89 + 1.07	15.2	220			
100	4	114.30 ± 0.23	6.02 + 0.71	07.6	110	8.56 + 1.02	11.0	160	11.10 + 1.32	15.2	220			
125	5	141.30 ± 0.25	6.55 + 0.79	06.5	90	9.52 + 1.14	09.7	140	12.70 + 1.52	13.7	200			
150	6	168.28 ± 0.28	7.11 + 0.86	06.5	90	10.97 + 1.32	09.7	140	14.27 + 1.70	13.1	190			
200	8	219.08 ± 0.38	8.18 + 0.99	05.5	80	12.70 + 1.52	08.3	120	-	-	-			

1 Mpa = 10 Kgf/cm², 1 Kgf/cm² = 14.20 psi

Note : Pressure rating of the pipes in threaded conditions reduces to half compared to unthreaded (aqua gold) pipes. These pipes are not recommended for solvent weld joints. #65mm (2½") pipe dimensions are as per company standard.

Joining Instructions



- While threading at the site, ensure square cut of the pipe ends, insert proper size wooden plug in the pipe end and then carry out threading. Adding cold water while threading improves the quality of threads.
- Use of cushion between jaws of the pipe wrench while holding the pipe is advisable to avoid damage to the pipe. It is recommended to use strap wrench for best results.
- The joint should be clean and threads should be made in one pass.
- For sealing of joints, best quality teflon tape must be used. This will avoid the damage to threads and avoid leakage.
- The joint should be made with hand tightening of the fitting over the pipe end covered with proper layer of teflon tape.
- Avoid over tightening of the joint.
- All the pipe lines should be supported approximately at a distance of 0.8 mtrs (2½') for horizontal service and 1.2 mtrs (4') for vertical service with pipe clips or CI brackets with nut bolts.
- When the system is to be concealed, it should be pressure tested before concealment.
- This system is not recommended for geyser outlets and hot water supply.
- In case of longer runs, provide air valves at all higher points of ground and the sizes of the valve should be ¼th of the main line.

The Supreme Industries Ltd. (Plastic Piping Division)

Corporate Office : 1161/1162, Solitair Corporate Park, Building No. 11, 167, Guru Hargovindji Marg, Chakala, Andheri Ghatkopar Link Road, Andheri (East) Mumbai - 400 093, India. Tel: 91-22-67710000, 40430000 Fax: 67710099 / 40430099.

Regd. Office : 612 Raheja Chambers, Nariman Point, Mumbai 400 021. India Tel.: (022) 22851656, 22820072 Fax : (91-22) 22851657

E-mail : pvc-pipes@supreme.co.in **Website :** www.supreme.co.in

Works : • D-101/102, MIDC, Jalgaon - 425 003.

• Unit No.3, Gat No.47-48, at post Gadegaon, Tal. Jamner, Dist., Jalgaon- 425 114

Export Division : 91-22-6771 0126 / 4043 0126 Fax : 6771 0130

Overseas Office : Sharjah, U.A.E. Tel # + 971 6 557 4484; Fax # + 971 6 557 4485

CIN: L35920MH1942PLC003554

Branch Offices Tel.

Ahmedabad	: 079-30028371	Fax	27680064
Bangalore	: 080-30913715		22104697
Chennai	: 044-39811181		43850498
Cochin	: 0484-2385346		2385345
Hyderabad	: 040-23261150		23261120
Indore	: 0731-2432684		2432684
Jaipur	: 09910995853		
Jalgaon	: 0257-3050541, 42		3050611
Kanpur	: 0512-2332276		2332276
Kolkata	: 033-30070123		24858838
Noida (Delhi)	: 0120-6660000		

Authorised Distributor

